



Commercial GFCI Receptacles

The new commercial GFCI receptacles feature an attractive new aesthetic look. A single rectangular LED indicator visually displays the device's ability to provide protection: green indicates power, red indicates a trip, and flashing red indicates end of life. Redesigned test and reset buttons provide a flush look and feel to the face of the receptacle.

Patented AUTOGUARD® self-test technology includes exclusive Closed Loop Active Detection (CLAD). Our advanced microcontroller identifies and isolates true ground fault conditions from transient events, harmonics, and other anomalous building noise, improving interoperability. Tamper-resistant (TR) listed models feature our patented shutter design for protection. Weather-resistant (WR) and combination tamper-resistant/weather-resistant (TRWR) models are also available.

Use Hubbell commercial GFCI receptacles for commercial installations in airports, office buildings, schools, and other facilities.

- Single LED indicator—power (green), trip ground fault (red), and end of life (flashing red)
- Patented AUTOGUARD® self-test and power denial technology
- Available in tamper-resistant and weather-resistant versions
- Available in black, brown, gray, white, ivory, light almond and red



Commercial GFCI Receptacles

ORDERING INFORMATION

Description	Color	15A	20A
Commercial grade ground fault receptacles, standard	Brown	GFR15	GFR20
	Black	GFR15BLK	GFR20BLK
	Gray	GFR15GRY	GFR20GRY
	Ivory	GFR15I	GFR20I
	Light Almond	GFR15LA	GFR20LA
	Red	GFR15R	GFR20R
	White	GFR15W	GFR20W
Commercial grade ground fault receptacles, tamper-resistant	Brown	GFRTR15	GFRTR20
	Black	GFRTR15BLK	GFRTR20BLK
	Gray	GFRTR15GRY	GFRTR20GRY
	Ivory	GFRTR15I	GFRTR20I
	Light Almond	GFRTR15LA	GFRTR20LA
	Red	GFRTR15R	GFRTR20R
	White	GFRTR15W	GFRTR20W
Commercial grade ground fault receptacles, weather-resistant	Brown	GFRWR15	GFRWR20
	Black	GFRWR15BLK	GFRWR20BLK
	Gray	GFRWR15GRY	GFRWR20GRY
	Ivory	GFRWR15I	GFRWR20I
	Light Almond	GFRWR15LA	GFRWR20LA
	Red	GFRWR15R	GFRWR20R
	White	GFRWR15W	GFRWR20W
Commercial grade ground fault receptacles, tamper and weather-resistant	Brown	GFRTW15	GFRTW20
	Black	GFRTW15BLK	GFRTW20BLK
	Gray	GFRTW15GRY	GFRTW20GRY
	Ivory	GFRTW15I	GFRTW20I
	Light Almond	GFRTW15LA	GFRTW20LA
	Red	GFRTW15R	GFRTW20R
	White	GFRTW15W	GFRTW20W



TECHNICAL INFORMATION

Ratings	
Amperage	15 Amp/20 Amp
Feed-through	20 Amp
Voltage	120V AC (- 15%, + 10%)
Frequency	60 Hz
Dielectric	Withstand 1,500V
Flammability	V0 per UL 94
Operating Temp	(-35°C to 66°C)
Trip Level	(4mA to 6mA) .025 sec.
Short Circuit	10,000 Amps

Certifications	
UL Listing	E41978 Fed Spec
UL Std 498	Receptacle
UL Std 943	GFCI
UL Std 943	Dust Resistant
UL Std 943	Corrosion Resistant
NEC®/CEC®	TR, WR Resistant
CSA Listing	LR24886
CSA Std	C22.2 No. 42
CSA Tech	No. M-02A

Construction	
Termination	Back and Side
Terminal	#14 to # 10AWG
Grounding	Autoground Clip
Power Indicator	Solid Green
GF/Trip Indicator	Solid Red
End of Life	Flashing Red
Contacts/Bridge	Nickel Plated
Printed Circuit Board	Conformal Coat
Scored Bridge	OEM Installations

Code and Standard Compliance

National Electric Code®

Compliant with NEC® 406.12 and NEC® 517-18c for Tamper-Resistance
Compliant with NEC® 406.9 for Weather Resistance

Industry Standards

NEMA WD6, ANSI C-73, NOM, National Electric Code,
Canadian Electric Code



A proud member of the Hubbell family.