# **PMXSPEC**<sup>®</sup> DESIGNED FOR THE MODERN WORKER



Experience unparalleled comfort with our lightweight safety glasses. Customizable fit, enhanced field of vision, superior protection, anti-fog clarity, and stylish design. Built tough to meet high impact standards and shield from UV rays. Ideal for long hours on the job.



#### **FEATURES**

**Unparalleled Comfort:** Experience the ultimate comfort with our lightweight safety glasses, ideal for long hours on the job

**Customized Fit:** The adjustable soft rubber nose piece and non-slip temple grips ensure a secure and comfortable fit in all conditions

**Enhanced Field of Vision:** The panoramic wraparound lens offers an extended field of vision, crucial for safety in busy work environments

**Superior Protection:** The large lens provides effective protection from wind, dust, and debris, ensuring eyes are protected at all times

**Anti-Fog Clarity:** The lens is treated with anti-fog properties to guarantee fog-free clarity, even in extreme conditions

**Stylish and Functional:** The lens is mirrored and beveled, reducing glare and adding a unique aesthetic appeal

**Built Tough:** Meets ANSI/ISEA Z87.1-2020 +, *Sectore and Sectore and Sectore* 



SB11265ST



SBL11257ST

PYRAMEX<sup>®</sup> **% # -- - 0 • \*** M P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM

# **PMXSPEC**<sup>®</sup> DESIGNED FOR THE MODERN WORKER

Experience unparalleled comfort with our lightweight safety glasses. Customizable fit, enhanced field of vision, superior protection, anti-fog clarity, and stylish design. Built tough to meet high impact standards and shield from UV rays. Ideal for long hours on the job.



mm

150 mm

Overall Width (hinge - hinge):

### VARIATIONS



### MATERIALS

Lens	Temples	Temple Tip	Nose Piece	Hinge
Polycarbonate	Polycarbonate	Rubber	Rubber	Polycarbonate

#### MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SB11265ST	P + S	P Z87 + / P c SEI Z94.3	P: Manufacturer's Mark	P: Manufacturer's Mark	Weight: 34 gm
SB11295ST	P + S	P Z87 + / P c SEI Z94.3	+: High Impact	Z87: ANSI/ISEA Z87.1-2020 Standard for Eye and Face Protection Devices +: High Impact	Lens Base: 6.5 base
SBL11257ST P+	P + S	P + S P Z87 + / P c SEI Z94.3	S: Special Purpose		Lens Size Diagonal: 147 mm
					Lens Size Vertical: 56 mm
				294.3: Certified for CAN/CSA Z94.3-20 Standard for Eye and Face Protection Devices	Lens Thickness: 2 mm
Product markings may vary // Updated as of 11.24					Overall Length (lens - tip): 153

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM